

ST606



артикул	мощность, W	световой поток, LM	цветовая температура, K	коэфф. цветопередачи, RA	угол рассеивания, °
■ ST606.432.12	led x 12	1080	3000	>90	120
■ ST606.442.12	led x 12	1080	4000	>90	120
□ ST606.532.12	led x 12	1080	3000	>90	120
□ ST606.542.12	led x 12	1080	4000	>90	120
■ ST606.432.27	led x 27	2430	3000	>90	120
■ ST606.442.27	led x 27	2430	4000	>90	120
□ ST606.532.27	led x 27	2430	3000	>90	120
□ ST606.542.27	led x 27	2430	4000	>90	120
■ ST606.432.36	led x 36	3240	3000	>90	120
■ ST606.442.36	led x 36	3240	4000	>90	120
□ ST606.532.36	led x 36	3240	3000	>90	120
□ ST606.542.36	led x 36	3240	4000	>90	120
■ ST606.432.48	led x 48	4320	3000	>90	120
■ ST606.442.48	led x 48	4320	4000	>90	120
□ ST606.532.48	led x 48	4320	3000	>90	120
□ ST606.542.48	led x 48	4320	4000	>90	120
■ ST606.432.96	led x 96	8640	3000	>90	120
■ ST606.442.96	led x 96	8640	4000	>90	120
□ ST606.532.96	led x 96	8640	3000	>90	120
□ ST606.542.96	led x 96	8640	4000	>90	120

накладные светильники 270



накладные светильники 271

